

Air is an Essential Part of Our Lives


WATER 1.2 kg(L)/person-day^{*2}

FOOD 1.3 kg/person-day*3 AIR 18 kg/person-day 15 m³ (Sphere diameter about 3 m)¹¹

Train and Humans - From a Physiological Viewpoint" (1999) by UCHIYAMA Iwao (National Institute of Public Health of Japan)
 Theat Stroke Environmental Health Manual (2009)" from the Ministry of the Environment, Government of Japan
 Basic Data Sheet of Agriculture, Forestry, and Fisheries, Statistics Regarding The Food Self-Sufficiency Rate" from Ministry of Agriculture, Forestry and Fisheries of Japan

What is Indoor Air Quality?

Indoor air quality (IAQ) indicates the quality of air in buildings such as homes, offices, public facilities, and schools. The quality of this air is vital to us leading healthy and comfortable lives.



Suppression of Bacteria Healthy and comfortable air current Suppression of bacteria and unpleasant odors

HEPA Composite Filter

- Comprises three innovative technologies: Super alleru-buster, Green Tea Catechin, and Anti-bacteria Enzyme
- Inhibits viruses, bacteria, and 17 kinds of allergen by up to 99% *1
- Effectively removes up to 99% of PM0.003 particles *2



- *1 Super alleru-buster (Report no. 2127)
 - Test Laboratory: Osaka Municipal Technical Research Institute of Japan. Test Methodology: Measure reduction level of tick allergens by Enzyme-linked Immuno Sorbent Assay. Inhibit Method: Contact with Super alleru-buster. Test Subject: Allergens captured by filter (tick, pollen, etc.). Test Results: 99% or more is inhibited.
- Catechin (Report no. 15-0115)

03

Test Laboratory: Kitasato Research Centre of Environmental Sciences. Test Methodology: Inhibit rate of virus using the Plaque method. Inhibit Method: Contact with Green Tea Catechin. Test Subject: Virus captured by filter. Test Results: 99% or more is inhibited.

Anti-bacteria Enzyme (Report no. 207060074-002)

Test Laboratory: Japan Food Research Laboratory. Test Methodology: Testing of the filter's anti-mold function using the Harrow method

*2 • PM0.003 particle (UN2-200911-T5599900-136)


Test Laboratory: IUTA. Test Subject: NaCl aerosol. Test Results: 3 nm particle removal efficiency >99.99%

De-formaldehyde Technology





With the additive substance, the formaldehyde is removed by means of chemical decomposition.



The porous activated carbon efficiently traps the formaldehyde contaminants.



The additive strengthens the trapping stability of the activated carbon against the contaminants.

3-steps to Eliminate Formaldehyde Contamination

Using the 3-step process, the formaldehyde contaminants are removed by chemical decomposition, activated carbon adsorption, and trapping.

Panasonic's Unique Technology

nanoe[™] comprises fine (5–20 nm), weakly acidic water particles that are reactive and hold an electric charge.nanoe™ also possesses anti-virus/ bacteria, deodorization, and skin hydration properties.

* 1 nm (nanometer) = one billionth of meter



nanoe[™] 10x Faster

• 10x faster air purification speed

nano

technology

• Greater efficiency for inhibiting viruses and bacteria Increases deodorization strength

l• nanoe

nano-technology + electric

÷

electric 🕑

and OH Radical —


4.8 trillion per second

(•nanoe X

Water Molecule -

nanoe™ (about 5-20 nm)


Goo re Efficient



nanoe[™]X and nanoe[™] Characteristics

Longer Life

Coated in water, nanoe™X and nanoe™ have six times longer life spans than ordinary air ion technology.



Safety of nanoe[™]X and nanoe[™] has been verified

Purpose	Test Name	Test Institute
Effect on Chromosomes	Chromosome abnormality test using cultured cells	Japan Bioassay Research Center ^[#1]
Effect on Respiratory System	Repeated administration toxicity test	Life Science Research Laboratory ^[#2]
Toxicological and Carcinogenic Impact	Chronic toxicity and carcinogenicity combined test	Food and Drug Safety Center, Hatano Research Institute [#1]
Effect on DNA	Comet assay	Food and Drug Safety Center, Hatano Research Institute [#1]

#1 The Japan Bioassay Research Center and the Food and Drug Safety Center, Hatano Research Institute are compliant with GLP (Good Laboratory Practice) (*1)

#2 Life Science Laboratories, Ltd. Is a registered institute of the Network of Organizations Investigating Accident Causes [*2] (*1) GLP is a practice intended to promote the quality and validity of test data used for determining the safety of chemicals and chemical products. Test facilities are assessed for compliance with GLP to ensure the reliability of their test data. (*2) The Network of Organizations Investigating Accident Causes is a network administered by National Institute of Technology and Evaluation under the Ministry of Economy, Trade and Industry,




Merits of nanoe™X – 3 main Features




Anti-virus/bacteria




SARS-CoV-2







07



Deodorization

Deeply penetrates into cloth fabrics for inhibiting odor

Novel Coronavirus (COVID-19)

[Testing organization] TEXCELL (France) [Testing method] Exposed to a nanoe™ device at 15cm distance in 45L enclosed box for 2 hours [Test substance] novel coronavirus (SARS-CoV-2) [Test results] Over 99.99% of activity is inhibited (1140-01 A1)

Influenza virus H1N1 subtype

[Testing organization] Kitasato Research Center for Environmental Science

[Testing method] Measured the number of viruses adhered to a cloth in an approximately $1 \ensuremath{m^3}$ airtight test room

[Inhibition method] nanoe™ released [Test substance] Adhered virus

[Test results] Inhibited by at least 99.9% in 2 hours (21_0084_1)

E. Coil (0157)

[Testing organization] Japan Food Research Laboratories [Testing method] Measured the number of bacteria adhered to a cloth in an approximately 45L airtight test room

[Inhibition method] nanoe™ released [Test substance] Adhered bacteria [Test results] Inhibited by at least 99.99% in 1 hour (208120880_001)

Reduces strong cigarette smoke odor to hardly noticeable in only 1 hour

Cigarette Smoke Odor


[Testing organization] Panasonic Product Analysis Center [Testing method] Verified using the six-level odor intensity scale method in an approximately 23m³ test room


[Deodorization method] nanoe™ released [Test substance] Surface-attached cigarette smoke odor [Test results] Odor intensity reduced by 2.4 levels in 12 mins. (4AA33-160615-N04)



Skin and Hair Hydration Helps keep the moisture back to the skin

Without nanoe™X












With nanoe™X


After 15 minutes

nanoeTM attaches to the sebum and forms a membrane over the skin, preventing moisture loss



After 28 days

Skin is hydrated, keeping it fresh and moisturized



Corneum
 Corneum

Sebum

Stratum

2.[Testing organization] FCG Research Institute, Inc. [Testing method and test results] Of 20 women 40 ± 2 years old, 10 women used a nanoe™ generating device at home for 28 days, while the other 10 women used a device with no nanoe™ generating device for 28 days at home (19104)



[Testing organization] Panasonic Product Analysis Center [Testing method and test results] Approximately 46m³ sized test room, room temperature 25 °C, humidity 40%, Bundles /6 bundles) of hair were suspended 2m from a nanoe¹¹⁴ generating device, with repeated operation of the nanoe¹¹⁴ generating device: 8 hours on and 16 hours off [Method] nanoe¹¹⁴ released [Test substance] Hair (USD-KS-15S-009-TM) Individual results may vary based on usage and seasonal/environmental variables (e.g., temperature and humidity)

PM2.5/Odor Indicator

The PM2.5 and odor indicator lets you to see the air quality easily and in real-time





"Superellipse" Design

Thanks to the aesthetics of "Superellipse", both art and functionality are achieved. The elegant and streamline look will really enhance your home.



Appliable Area: 52 m²

Dimensions: H 560 x W 362 x D 280 mm | Weight: 8 kg

Air Purification

nanoe™X HEPA Composite Filter Super Nano-technology Deodorizing Filter De-Formaldehyde Function

Other Features

PM2.5 / Odor Sensor Brightness Sensor Child Lock

Indicator

LCD Indication Panel PM2.5 Concentration Digital Indicator Odor Level Indicator Filter Replacement Indicator



Power ON/OFF Brightness Sensor

	Air Purification		
Setting	High	Mid	Low
Power Consumption [W]	36	10.5	6.5
Air Volume [m³/min.]	7	3.1	1.1
Noise [dB(A)]	48	32	18

Note:

The calculation of applicable area is based on the standard JEM1467, as stipulated by the Japan Electrical Manufacturers Association. The applicable area is defined as the area filled with dirty air, 30 mins under 1 air change per hour of natural ventilation, as specified under the Building Sanitation Law.